

# Apache Performance Notes

## Warning:

This document has not been fully updated to take into account changes made in the 2.0 version of the Apache HTTP Server. Some of the information may still be relevant, but please use it with care.

Originally written by Dean Gaudet.

Apache 2.0 is a general-purpose webserver, designed to provide a balance of flexibility, portability, and performance. Although it has not been designed specifically to set benchmark records, Apache 2.0 is capable of high performance in many real-world situations.

Compared to Apache 1.3, release 2.0 contains many additional optimizations to increase throughput and scalability. Most of these improvements are enabled by default. However, there are compile-time and run-time configuration choices that can significantly affect performance. This document describes the options that a server administrator can configure to tune the performance of an Apache 2.0 installation. Some of these configuration options enable the httpd to better take advantage of the capabilities of the hardware and OS, while others allow the administrator to trade functionality for speed.

## Topics

Hardware and Operating System Issues .....	1
Run-Time Configuration Issues .....	1
Compile-Time Configuration Issues .....	5
Appendix: Detailed Analysis of a Trace .....	9
URI References .....	11

## Hardware and Operating System Issues

---

The single biggest hardware issue affecting webserver performance is RAM. A webserver should never ever have to swap, swapping increases the latency of each request beyond a point that users consider "fast enough". This causes users to hit stop and reload, further increasing the load. You can, and should, control the `MaxClients` setting so that your server does not spawn so many children it starts swapping.

Beyond that the rest is mundane: get a fast enough CPU, a fast enough network card, and fast enough disks, where "fast enough" is something that needs to be determined by experimentation.

Operating system choice is largely a matter of local concerns. But some guidelines that have proven generally useful are:

- Run the latest stable release and patchlevel of the operating system that you choose. Many OS suppliers have introduced significant performance improvements to their TCP stacks and thread libraries in recent years.
- If your OS supports a `sendfile(2)` system call, make sure you install the release and/or patches needed to enable it. (With Linux, for example, this means using Linux 2.4 or later. For early releases of Solaris 8, you may need to apply a patch.) On systems where it is available, `sendfile` enables Apache 2 to deliver static content faster and with lower CPU utilization.

## Run-Time Configuration Issues

---

Apache Performance Notes

---

Related Modules	Related Directives
<code>mod_dir</code>	<code>AllowOverride</code>
<code>mpm_common</code>	<code>DirectoryIndex</code>
<code>mod_status</code>	<code>HostnameLookups</code>
	<code>EnableMMAP</code>
	<code>EnableSendfile</code>
	<code>KeepAliveTimeout</code>
	<code>MaxSpareServers</code>
	<code>MinSpareServers</code>
	<code>Options</code>
	<code>StartServers</code>

## HostnameLookups

Prior to Apache 1.3, `HostnameLookups` defaulted to `On`. This adds latency to every request because it requires a DNS lookup to complete before the request is finished. In Apache 1.3 this setting defaults to `Off`. However (1.3 or later), if you use any `Allow` from `domain` or `Deny` from `domain` directives then you will pay for a double reverse DNS lookup (a reverse, followed by a forward to make sure that the reverse is not being spoofed). So for the highest performance avoid using these directives (it's fine to use IP addresses rather than domain names).

Note that it's possible to scope the directives, such as within a `<Location /server-status>` section. In this case the DNS lookups are only performed on requests matching the criteria. Here's an example which disables lookups except for `.html` and `.cgi` files:

```
HostnameLookups off
<Files ~ "\.(html|cgi)$">
  HostnameLookups on
</Files>
```

But even still, if you just need DNS names in some CGIs you could consider doing the `gethostbyname` call in the specific CGIs that need it.

Similarly, if you need to have hostname information in your server logs in order to generate reports of this information, you can postprocess your log file with `logresolve`<sup>1</sup>, so that these lookups can be done without making the client wait. It is recommended that you do this postprocessing, and any other statistical analysis of the log file, somewhere other than your production web server machine, in order that this activity does not adversely affect server performance.

## FollowSymLinks and SymLinksIfOwnerMatch

Wherever in your URL-space you do not have an `Options FollowSymLinks`, or you do have an `Options SymLinksIfOwnerMatch` Apache will have to issue extra system calls to check up on symlinks. One extra call per filename component. For example, if you had:

```
DocumentRoot /www/htdocs
<Directory />
  Options SymLinksIfOwnerMatch
</Directory>
```

and a request is made for the URI `/index.html`. Then Apache will perform `lstat(2)` on `/www`, `/www/htdocs`, and `/www/htdocs/index.html`. The results of these `lstats` are never cached, so they will occur on every single request. If you really desire the symlinks security checking you can do something like this:

---

## Apache Performance Notes

---

```
DocumentRoot /www/htdocs
<Directory />
  Options FollowSymLinks
</Directory>

<Directory /www/htdocs>
  Options -FollowSymLinks +SymLinksIfOwnerMatch
</Directory>
```

This at least avoids the extra checks for the `DocumentRoot` path. Note that you'll need to add similar sections if you have any `Alias` or `RewriteRule` paths outside of your document root. For highest performance, and no symlink protection, set `FollowSymLinks` everywhere, and never set `SymLinksIfOwnerMatch`.

### AllowOverride

Wherever in your URL-space you allow overrides (typically `.htaccess` files) Apache will attempt to open `.htaccess` for each filename component. For example,

```
DocumentRoot /www/htdocs
<Directory />
  AllowOverride all
</Directory>
```

and a request is made for the URI `/index.html`. Then Apache will attempt to open `/.htaccess`, `/www/.htaccess`, and `/www/htdocs/.htaccess`. The solutions are similar to the previous case of `Options FollowSymLinks`. For highest performance use `AllowOverride None` everywhere in your filesystem.

### Negotiation

If at all possible, avoid content-negotiation if you're really interested in every last ounce of performance. In practice the benefits of negotiation outweigh the performance penalties. There's one case where you can speed up the server. Instead of using a wildcard such as:

```
DirectoryIndex index
```

Use a complete list of options:

```
DirectoryIndex index.cgi index.pl index.shtml index.html
```

where you list the most common choice first.

Also note that explicitly creating a `type-map` file provides better performance than using `MultiViews`, as the necessary information can be determined by reading this single file, rather than having to scan the directory for files.

### Memory-mapping

In situations where Apache 2.0 needs to look at the contents of a file being delivered--for example, when doing server-side-include processing--it normally memory-maps the file if the OS supports some form of `mmap(2)`.

On some platforms, this memory-mapping improves performance. However, there are cases where memory-mapping can hurt the performance or even the stability of the `httpd`:

---

## Apache Performance Notes

---

- On some operating systems, `mmap` does not scale as well as `read(2)` when the number of CPUs increases. On multiprocessor Solaris servers, for example, Apache 2.0 sometimes delivers server-parsed files faster when `mmap` is disabled.
- If you memory-map a file located on an NFS-mounted filesystem and a process on another NFS client machine deletes or truncates the file, your process may get a bus error the next time it tries to access the mapped file content.

For installations where either of these factors applies, you should use `EnableMMAP off` to disable the memory-mapping of delivered files. (Note: This directive can be overridden on a per-directory basis.)

### Sendfile

In situations where Apache 2.0 can ignore the contents of the file to be delivered -- for example, when serving static file content -- it normally uses the kernel `sendfile` support the file if the OS supports the `sendfile(2)` operation.

On most platforms, using `sendfile` improves performance by eliminating separate read and send mechanics. However, there are cases where using `sendfile` can harm the stability of the `httpd`:

- Some platforms may have broken `sendfile` support that the build system did not detect, especially if the binaries were built on another box and moved to such a machine with broken `sendfile` support.
- With an NFS-mounted files, the kernel may be unable to reliably serve the network file through it's own cache.

For installations where either of these factors applies, you should use `EnableSendfile off` to disable `sendfile` delivery of file contents. (Note: This directive can be overridden on a per-directory basis.)

### Process Creation

Prior to Apache 1.3 the `MinSpareServers`, `MaxSpareServers`, and `StartServers` settings all had drastic effects on benchmark results. In particular, Apache required a "ramp-up" period in order to reach a number of children sufficient to serve the load being applied. After the initial spawning of `StartServers` children, only one child per second would be created to satisfy the `MinSpareServers` setting. So a server being accessed by 100 simultaneous clients, using the default `StartServers` of 5 would take on the order 95 seconds to spawn enough children to handle the load. This works fine in practice on real-life servers, because they aren't restarted frequently. But does really poorly on benchmarks which might only run for ten minutes.

The one-per-second rule was implemented in an effort to avoid swamping the machine with the startup of new children. If the machine is busy spawning children it can't service requests. But it has such a drastic effect on the perceived performance of Apache that it had to be replaced. As of Apache 1.3, the code will relax the one-per-second rule. It will spawn one, wait a second, then spawn two, wait a second, then spawn four, and it will continue exponentially until it is spawning 32 children per second. It will stop whenever it satisfies the `MinSpareServers` setting.

This appears to be responsive enough that it's almost unnecessary to twiddle the `MinSpareServers`, `MaxSpareServers` and `StartServers` knobs. When more than 4 children are spawned per second, a message will be emitted to the `ErrorLog`. If you see a lot of these errors then consider tuning these settings. Use the `mod_status` output as a guide.

Related to process creation is process death induced by the `MaxRequestsPerChild` setting. By default this is 0, which means that there is no limit to the number of requests handled per child. If your configuration currently has this set to some very low number, such as 30, you may want to bump this

up significantly. If you are running SunOS or an old version of Solaris, limit this to 10000 or so because of memory leaks.

When keep-alives are in use, children will be kept busy doing nothing waiting for more requests on the already open connection. The default `KeepAliveTimeout` of 15 seconds attempts to minimize this effect. The tradeoff here is between network bandwidth and server resources. In no event should you raise this above about 60 seconds, as most of the benefits are lost<sup>2</sup>.

## Compile-Time Configuration Issues

---

### `mod_status` and `ExtendedStatus On`

If you include `mod_status` and you also set `ExtendedStatus On` when building and running Apache, then on every request Apache will perform two calls to `gettimeofday(2)` (or `times(2)` depending on your operating system), and (pre-1.3) several extra calls to `time(2)`. This is all done so that the status report contains timing indications. For highest performance, set `ExtendedStatus off` (which is the default).

### `accept` Serialization - multiple sockets

This discusses a shortcoming in the Unix socket API. Suppose your web server uses multiple `Listen` statements to listen on either multiple ports or multiple addresses. In order to test each socket to see if a connection is ready Apache uses `select(2)`. `select(2)` indicates that a socket has *zero* or *at least one* connection waiting on it. Apache's model includes multiple children, and all the idle ones test for new connections at the same time. A naive implementation looks something like this (these examples do not match the code, they're contrived for pedagogical purposes):

```
for (;;) {
  for (;;) {
    fd_set accept_fds;

    FD_ZERO (&accept_fds);
    for (i = first_socket; i <= last_socket; ++i) {
      FD_SET (i, &accept_fds);
    }
    rc = select (last_socket+1, &accept_fds, NULL, NULL, NULL);
    if (rc < 1) continue;
    new_connection = -1;
    for (i = first_socket; i <= last_socket; ++i) {
      if (FD_ISSET (i, &accept_fds)) {
        new_connection = accept (i, NULL, NULL);
        if (new_connection != -1) break;
      }
    }
    if (new_connection != -1) break;
  }
  process the new_connection;
}
```

But this naive implementation has a serious starvation problem. Recall that multiple children execute this loop at the same time, and so multiple children will block at `select` when they are in between requests. All those blocked children will awaken and return from `select` when a single request appears on any socket (the number of children which awaken varies depending on the operating system and timing issues). They will all then fall down into the loop and try to `accept` the connection. But only one will succeed (assuming there's still only one connection ready), the rest will be *blocked* in `accept`. This effectively locks those children into serving requests from that one socket and no other sockets, and they'll be stuck there until enough new requests appear on that socket to wake them all up. This starvation problem was first documented in PR#467<sup>3</sup>. There are at least two solutions.

---

 Apache Performance Notes
 

---

One solution is to make the sockets non-blocking. In this case the `accept` won't block the children, and they will be allowed to continue immediately. But this wastes CPU time. Suppose you have ten idle children in `select`, and one connection arrives. Then nine of those children will wake up, try to accept the connection, fail, and loop back into `select`, accomplishing nothing. Meanwhile none of those children are servicing requests that occurred on other sockets until they get back up to the `select` again. Overall this solution does not seem very fruitful unless you have as many idle CPUs (in a multiprocessor box) as you have idle children, not a very likely situation.

Another solution, the one used by Apache, is to serialize entry into the inner loop. The loop looks like this (differences highlighted):

```

for (;;) {
  accept_mutex_on ();
  for (;;) {
    fd_set accept_fds;

    FD_ZERO (&accept_fds);
    for (i = first_socket; i <= last_socket; ++i) {
      FD_SET (i, &accept_fds);
    }
    rc = select (last_socket+1, &accept_fds, NULL, NULL, NULL);
    if (rc < 1) continue;
    new_connection = -1;
    for (i = first_socket; i <= last_socket; ++i) {
      if (FD_ISSET (i, &accept_fds)) {
        new_connection = accept (i, NULL, NULL);
        if (new_connection != -1) break;
      }
    }
    if (new_connection != -1) break;
  }
  accept_mutex_off ();
  process the new_connection;
}

```

The functions `accept_mutex_on` and `accept_mutex_off` implement a mutual exclusion semaphore. Only one child can have the mutex at any time. There are several choices for implementing these mutexes. The choice is defined in `src/conf.h` (pre-1.3) or `src/include/ap_config.h` (1.3 or later). Some architectures do not have any locking choice made, on these architectures it is unsafe to use multiple `Listen` directives.

**USE\_FLOCK\_SERIALIZED\_ACCEPT**

This method uses the `flock(2)` system call to lock a lock file (located by the `LockFile` directive).

**USE\_FCNTL\_SERIALIZED\_ACCEPT**

This method uses the `fcntl(2)` system call to lock a lock file (located by the `LockFile` directive).

**USE\_SYSVSEM\_SERIALIZED\_ACCEPT**

(1.3 or later) This method uses SysV-style semaphores to implement the mutex. Unfortunately SysV-style semaphores have some bad side-effects. One is that it's possible Apache will die without cleaning up the semaphore (see the `ipcs(8)` man page). The other is that the semaphore API allows for a denial of service attack by any CGIs running under the same uid as the webserver (*i.e.*, all CGIs, unless you use something like `suexec` or `cgiwrapper`). For these reasons this method is not used on any architecture except IRIX (where the previous two are prohibitively expensive on most IRIX boxes).

**USE\_USLOCK\_SERIALIZED\_ACCEPT**

(1.3 or later) This method is only available on IRIX, and uses `usconfig(2)` to create a mutex.

---

## Apache Performance Notes

---

While this method avoids the hassles of SysV-style semaphores, it is not the default for IRIX. This is because on single processor IRIX boxes (5.3 or 6.2) the `uslock` code is two orders of magnitude slower than the SysV-semaphore code. On multi-processor IRIX boxes the `uslock` code is an order of magnitude faster than the SysV-semaphore code. Kind of a messed up situation. So if you're using a multiprocessor IRIX box then you should rebuild your webserver with `-DUSE_USLOCK_SERIALIZED_ACCEPT` on the `EXTRA_CFLAGS`.

### **USE\_PTHREAD\_SERIALIZED\_ACCEPT**

(1.3 or later) This method uses POSIX mutexes and should work on any architecture implementing the full POSIX threads specification, however appears to only work on Solaris (2.5 or later), and even then only in certain configurations. If you experiment with this you should watch out for your server hanging and not responding. Static content only servers may work just fine.

If your system has another method of serialization which isn't in the above list then it may be worthwhile adding code for it (and submitting a patch back to Apache).

Another solution that has been considered but never implemented is to partially serialize the loop -- that is, let in a certain number of processes. This would only be of interest on multiprocessor boxes where it's possible multiple children could run simultaneously, and the serialization actually doesn't take advantage of the full bandwidth. This is a possible area of future investigation, but priority remains low because highly parallel web servers are not the norm.

Ideally you should run servers without multiple `Listen` statements if you want the highest performance. But read on.

### **accept Serialization - single socket**

The above is fine and dandy for multiple socket servers, but what about single socket servers? In theory they shouldn't experience any of these same problems because all children can just block in `accept(2)` until a connection arrives, and no starvation results. In practice this hides almost the same "spinning" behaviour discussed above in the non-blocking solution. The way that most TCP stacks are implemented, the kernel actually wakes up all processes blocked in `accept` when a single connection arrives. One of those processes gets the connection and returns to user-space, the rest spin in the kernel and go back to sleep when they discover there's no connection for them. This spinning is hidden from the user-land code, but it's there nonetheless. This can result in the same load-spiking wasteful behaviour that a non-blocking solution to the multiple sockets case can.

For this reason we have found that many architectures behave more "nicely" if we serialize even the single socket case. So this is actually the default in almost all cases. Crude experiments under Linux (2.0.30 on a dual Pentium pro 166 w/128Mb RAM) have shown that the serialization of the single socket case causes less than a 3% decrease in requests per second over unserialized single-socket. But unserialized single-socket showed an extra 100ms latency on each request. This latency is probably a wash on long haul lines, and only an issue on LANs. If you want to override the single socket serialization you can define `SINGLE_LISTEN_UNSERIALIZED_ACCEPT` and then single-socket servers will not serialize at all.

### **Lingering Close**

As discussed in draft-ietf-http-connection-00.txt<sup>4</sup> section 8, in order for an HTTP server to **reliably** implement the protocol it needs to shutdown each direction of the communication independently (recall that a TCP connection is bi-directional, each half is independent of the other). This fact is often overlooked by other servers, but is correctly implemented in Apache as of 1.2.

When this feature was added to Apache it caused a flurry of problems on various versions of Unix because of a shortsightedness. The TCP specification does not state that the `FIN_WAIT_2` state has a

---

## Apache Performance Notes

---

timeout, but it doesn't prohibit it. On systems without the timeout, Apache 1.2 induces many sockets stuck forever in the `FIN_WAIT_2` state. In many cases this can be avoided by simply upgrading to the latest TCP/IP patches supplied by the vendor. In cases where the vendor has never released patches (*i.e.*, SunOS4 -- although folks with a source license can patch it themselves) we have decided to disable this feature.

There are two ways of accomplishing this. One is the socket option `SO_LINGER`. But as fate would have it, this has never been implemented properly in most TCP/IP stacks. Even on those stacks with a proper implementation (*i.e.*, Linux 2.0.31) this method proves to be more expensive (cputime) than the next solution.

For the most part, Apache implements this in a function called `lingering_close` (in `http_main.c`). The function looks roughly like this:

```
void lingering_close (int s)
{
    char junk_buffer[2048];

    /* shutdown the sending side */
    shutdown (s, 1);

    signal (SIGALRM, lingering_death);
    alarm (30);

    for (;;) {
        select (s for reading, 2 second timeout);
        if (error) break;
        if (s is ready for reading) {
            if (read (s, junk_buffer, sizeof (junk_buffer)) <= 0) {
                break;
            }
            /* just toss away whatever is here */
        }
    }

    close (s);
}
```

This naturally adds some expense at the end of a connection, but it is required for a reliable implementation. As HTTP/1.1 becomes more prevalent, and all connections are persistent, this expense will be amortized over more requests. If you want to play with fire and disable this feature you can define `NO_LINGCLOSE`, but this is not recommended at all. In particular, as HTTP/1.1 pipelined persistent connections come into use `lingering_close` is an absolute necessity (and pipelined connections are faster<sup>5</sup>, so you want to support them).

### Scoreboard File

Apache's parent and children communicate with each other through something called the scoreboard. Ideally this should be implemented in shared memory. For those operating systems that we either have access to, or have been given detailed ports for, it typically is implemented using shared memory. The rest default to using an on-disk file. The on-disk file is not only slow, but it is unreliable (and less featured). Peruse the `src/main/conf.h` file for your architecture and look for either `USE_MMAP_SCOREBOARD` or `USE_SHMGET_SCOREBOARD`. Defining one of those two (as well as their companions `HAVE_MMAP` and `HAVE_SHMGET` respectively) enables the supplied shared memory code. If your system has another type of shared memory, edit the file `src/main/http_main.c` and add the hooks necessary to use it in Apache. (Send us back a patch too please.)

Historical note: The Linux port of Apache didn't start to use shared memory until version 1.2 of Apache. This oversight resulted in really poor and unreliable behaviour of earlier versions of

Apache on Linux.

## DYNAMIC\_MODULE\_LIMIT

If you have no intention of using dynamically loaded modules (you probably don't if you're reading this and tuning your server for every last ounce of performance) then you should add `--DDYNAMIC_MODULE_LIMIT=0` when building your server. This will save RAM that's allocated only for supporting dynamically loaded modules.

## Appendix: Detailed Analysis of a Trace

---

Here is a system call trace of Apache 2.0.38 with the worker MPM on Solaris 8. This trace was collected using:

```
truss -l -p httpd_child_pid.
```

The `-l` option tells `truss` to log the ID of the LWP (lightweight process--Solaris's form of kernel-level thread) that invokes each system call.

Other systems may have different system call tracing utilities such as `strace`, `ktrace`, or `par`. They all produce similar output.

In this trace, a client has requested a 10KB static file from the `httpd`. Traces of non-static requests or requests with content negotiation look wildly different (and quite ugly in some cases).

```
/67:  accept(3, 0x00200BEC, 0x00200C0C, 1) (sleeping...)
/67:  accept(3, 0x00200BEC, 0x00200C0C, 1)                = 9
```

In this trace, the listener thread is running within LWP #67.

Note the lack of `accept(2)` serialization. On this particular platform, the worker MPM uses an unserialized `accept` by default unless it is listening on multiple ports.

```
/65:  lwp_park(0x00000000, 0)                                = 0
/67:  lwp_unpark(65, 1)                                     = 0
```

Upon accepting the connection, the listener thread wakes up a worker thread to do the request processing. In this trace, the worker thread that handles the request is mapped to LWP #65.

```
/65:  getsockname(9, 0x00200BA4, 0x00200BC4, 1)            = 0
```

In order to implement virtual hosts, Apache needs to know the local socket address used to accept the connection. It is possible to eliminate this call in many situations (such as when there are no virtual hosts, or when `Listen` directives are used which do not have wildcard addresses). But no effort has yet been made to do these optimizations.

---

 Apache Performance Notes
 

---

```
/65: brk(0x002170E8) = 0
/65: brk(0x002190E8) = 0
```

The `brk(2)` calls allocate memory from the heap. It is rare to see these in a system call trace, because the `httpd` uses custom memory allocators (`apr_pool` and `apr_bucket_alloc`) for most request processing. In this trace, the `httpd` has just been started, so it must call `malloc(3)` to get the blocks of raw memory with which to create the custom memory allocators.

```
/65: fcntl(9, F_GETFL, 0x00000000) = 2
/65: fstat64(9, 0xFAF7B818) = 0
/65: getsockopt(9, 65535, 8192, 0xFAF7B918, 0xFAF7B910, 2190656) = 0
/65: fstat64(9, 0xFAF7B818) = 0
/65: getsockopt(9, 65535, 8192, 0xFAF7B918, 0xFAF7B914, 2190656) = 0
/65: setsockopt(9, 65535, 8192, 0xFAF7B918, 4, 2190656) = 0
/65: fcntl(9, F_SETFL, 0x00000082) = 0
```

Next, the worker thread puts the connection to the client (file descriptor 9) in non-blocking mode. The `setsockopt(2)` and `getsockopt(2)` calls are a side-effect of how Solaris's `libc` handles `fcntl(2)` on sockets.

```
/65: read(9, " G E T / 1 0 k . h t m"..., 8000) = 97
```

The worker thread reads the request from the client.

```
/65: stat("/var/httpd/apache/httpd-8999/htdocs/10k.html", 0xFAF7B978) = 0
/65: open("/var/httpd/apache/httpd-8999/htdocs/10k.html", O_RDONLY) = 10
```

This `httpd` has been configured with `Options FollowSymLinks` and `AllowOverride None`. Thus it doesn't need to `lstat(2)` each directory in the path leading up to the requested file, nor check for `.htaccess` files. It simply calls `stat(2)` to verify that the file: 1) exists, and 2) is a regular file, not a directory.

```
/65: sendfilev(0, 9, 0x00200F90, 2, 0xFAF7B53C) = 10269
```

In this example, the `httpd` is able to send the HTTP response header and the requested file with a single `sendfilev(2)` system call. Sendfile semantics vary among operating systems. On some other systems, it is necessary to do a `write(2)` or `writenv(2)` call to send the headers before calling `sendfile(2)`.

```
/65: write(4, " 1 2 7 . 0 . 0 . 1 -"..., 78) = 78
```

This `write(2)` call records the request in the access log. Note that one thing missing from this trace is a `time(2)` call. Unlike Apache 1.3, Apache 2.0 uses `gettimeofday(3)` to look up the time. On some operating systems, like Linux or Solaris, `gettimeofday` has an optimized implementation that doesn't require as much overhead as a typical system call.

---

### Apache Performance Notes

---

```
/65: shutdown(9, 1, 1) = 0
/65: poll(0xFAF7B980, 1, 2000) = 1
/65: read(9, 0xFAF7BC20, 512) = 0
/65: close(9) = 0
```

The worker thread does a lingering close of the connection.

```
/65: close(10) = 0
/65: lwp_park(0x00000000, 0) (sleeping...)
```

Finally the worker thread closes the file that it has just delivered and blocks until the listener assigns it another connection.

```
/67: accept(3, 0x001FEB74, 0x001FEB94, 1) (sleeping...)
```

Meanwhile, the listener thread is able to accept another connection as soon as it has dispatched this connection to a worker thread (subject to some flow-control logic in the worker MPM that throttles the listener if all the available workers are busy). Though it isn't apparent from this trace, the next `accept(2)` can (and usually does, under high load conditions) occur in parallel with the worker thread's handling of the just-accepted connection.

## URI References

---

- [1] <http://httpd.apache.org/docs-2.1/programs/logresolve.html>
- [2] <http://www.research.digital.com/wrl/techreports/abstracts/95.4.html>
- [3] <http://bugs.apache.org/index/full/467>
- [4] <http://www.ics.uci.edu/pub/ietf/http/draft-ietf-http-connection-00.txt>
- [5] <http://www.w3.org/Protocols/HTTP/Performance/Pipeline.html>